

Hand Pallet Truck

HULKMAN

Model: BF

1KG=2.205LB 1INCH=25.40MM

Model		BF	
Capacity	Q(kg)	2500/3000	2500/3000
Lowered fork height	h_1 (mm)	85	75
Steering wheel	mm	φ 200	φ 180
Fork wheel single	mm	φ 80x93	φ 74x93
Fork wheel tandem	mm	φ 80x70	φ 74x70
Max. lift height	h_2 (mm)	200	190
Total height	h_3 (mm)	1224	1214
Overall length	L (mm)	1483/1533/1603	1483/1533/1603
Fork length	l (mm)	1100/1150/1220	1100/1150/1220
Width overall forks	b_1 (mm)	520/550/685	520/550/685
Ground clearance, centre of wheelbase	m_1 (mm)	40	30
Aisle width for pallets 1000x1200 crossways	A_1 (mm)	1683/1733/1803	1683/1733/1803
Aisle width for pallets 800x1200 lengthways	A_2 (mm)	1783/1783/1803	1783/1783/1803
Turning radius	W (mm)	1216/1266/1336	1216/1266/1336
Service weight	kg	60-75	60-75

Over
5,000,000
units sold



Innovative design, comprehensive testing and highest quality !

- Most standard and popular model with capacity 2500 - 3000kgs.
- With Copping Supporting NOG & strengthening ribbing under top triangle cover.
- Complete pump design with reliable leak-proof pump eliminating maintenance and extending the service time.
- 210 steering arc, and small turning radius.
- Fork Lowering speed is controllable, operated by hand control and foot pedal.
- Entry / exit roller, more freely travel.
- Equipped with over-load valve, with long service time.
- 3 position hand control - Raise, Lower, Neutral.
- 12 lubrication grease nipples on all movable parts for easy maintenance.
- Adjustable pump cap ensures a long service life.
- Ergonomic large rubber handle with three control lever.
- Option: 1) Nylon wheel, polyurethane wheel, rubber wheel, single fork roller or tandem fork rollers.
2) Fork length: 800mm, 900mm, 1000mm.
3) Foot pedal release.
4) Pump color: black painting, silver painting.



Conforms to EN ISO3691-5
Based on Directive 2006/42/EC

Professional



Option: fully rubber wrapped handle




Adjustable pump cap



Adjustable straight tappet



Additional entry and exit roller



Remark: Special size fork width and length can be made according to customer's requirement.